(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 27 January 2005 (27.01.2005)

(10) International Publication Number WO 2005/008622 A1

(51) International Patent Classification7:

G09G 3/32

(21) International Application Number:

PCT/IB2004/002291

(22) International Filing Date:

7 July 2004 (07.07.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0316862.2

18 July 2003 (18.07.2003)


- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): JOHNSON, Mark, T. [GB/GB]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB). FISEKOVIC, Nebojsa [YU/NL]; c/o Philips Intellectual

Property & Standards, Cross Oak Lane, Redhill, Surrey RIII 5IIA (GB).

- (74) Agent: WILLIAMSON, Paul, L.; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RIII SIIA (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AB, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH. PL. PT. RO. RU. SC. SD. SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Burasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IB, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: OLED DISPLAY DEVICE



having a current driven emissive element, a data input for receiving an analogue data signal, at least one drive element connected to a power supply and arranged to drive the current emissive element in accordance with the data signal and selecting means arranged to provide, in response to a select signal, the data signal to the at least one drive element to generate an overall brightness level during a frame period in accordance with the data signal. The device is adapted to divide the frame period in at least a first sub-period during which the emissive element carries a first non-zero current and a second sub-period during which the emissive element carries a second non-zero current, the at least first and second non-zero current yielding the overall brightness level.